

## DIGITAL INSTANT HOT WATER DISPENSER

## No More Waiting for Hot Water!



## **KEY FEATURES SUMMARY**

- Digital Soft-Touch Control Panel
- On/Off Button with Vacation-Mode
- Seven Pre-Set Temperatures = 167°-208°F
- Temperature Settings = 3° increments
- Digital Temperature Control Within 1–2°
- Patent Pending Engineering
- Built-In Dry Burn and Overheat Sensors
- Built-In 60 psi PRV w/Patented Baffle Fill System
- 304 Stainless Steel Tank 0.6 USG (2.4 litres)
- Encased Element Prevents Limescale Build-Up
- Double Venturi Reduces Faucet "Dripping/Spitting"
- 60-Cups Per Hour Capacity
- Cold Start Up 8-10 minutes
- Reheat After Use 4–5–minutes

- PSU 5V
- Standby Power 1W
- 1500-Watt/120-Volt Rapid-Recovery Element
- Standby Reheat @ 6° Temperature–Drop
- Quality Metal Housing with 4 Base Mounted Feet
- Cabinet-Side or Floor-Mount Install Options
- Space-Saving 7.5" W x 7.5" D x 10.75" H
- Compatible with RO Filtration Systems
- Compatible with all BTI Aqua-Solutions Faucets
- 4-Pack Master Carton
- UL Certified
- USA/Canada Electrical Approvals
- 5-Year Warranty